

JETTING TRIGGERAIR	CABLE DIAMETER IN MM	0.8	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40																										
	DUCT DIAMETER IN MM				3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63			
		USAGE												FTTH											BLOWING DISTANCE											500 m+ (1640 feet+)											AIR CONNECTION											Std 3/8" Cejn										
		MAX SPEED												150 m/min (492 ft/min)											MIN/MAX PRESSURE											8-16 Bar (120-230 psi)											COMPRESSOR AIRFLOW											100-150 L /min. (3.5- 7.0 cfm)										
		CABLE DIAMETER												0.8 – 3 mm											WxHxD (HARD CASE)											460 x 370 x 180 mm (18.1x13.8~7.1 in.)																																
		DUCT DIAMETER												3, 5, 7, 8 mm											WEIGHT											Approx 2,3 kg (13,9 lb)																																
PUSHING FORCE												Up to 30 N (Up to 6.74 lbf)											BATTERY											12V, 4Ah Milwaukee																																		
JETTING VO	CABLE DIAMETER IN MM	0.8	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40																										
	DUCT DIAMETER IN MM				3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63			
		USAGE												FTTH											BLOWING DISTANCE											1000 m+ (3280 feet+)											AIR CONNECTION											Std 3/8" Cejn										
		MAX SPEED												250 m/min (820 ft/min)											MIN/MAX PRESSURE											8-16 Bar (120-230 psi)											WORKS WITH JETLOGGER											☒										
		CABLE DIAMETER												0.8 – 6.0 mm											WxHxD (HARD CASE)											600x500x300 mm (4.72x8.66~6.69 inches)											COMPRESSOR AIRFLOW											100-600 L /min. (3.5- 21 cfm)										
		DUCT DIAMETER												3 – 16 mm											WEIGHT											Approx 13 kg (4.4 lb)																																
PUSHING FORCE												Up to 60 N (Up to 13.5 lbf)											BATTERY											18 V, 5Ah Milwaukee																																		
JETTING VO HD	CABLE DIAMETER IN MM	0.8	1	2	3	4	5	6,5	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40																										
	DUCT DIAMETER IN MM				3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63			
		USAGE												FTTH											BLOWING DISTANCE											1500 m + (4900 feet+)											AIR CONNECTION											Std 3/8" Cejn										
		MAX SPEED												110 m/min (361 ft/min)											MIN/MAX PRESSURE											8-16 Bar (120-230 psi)											WORKS WITH JETLOGGER											☒										
		CABLE DIAMETER												0.8 – 6.5 mm											WxHxD (HARD CASE)											600 x 500 x 300 mm (4.72x8.66~6.69 in.)											COMPRESSOR AIRFLOW											100-600 L /min. (3.5- 21 cfm)										
		DUCT DIAMETER												3 – 16 mm											WEIGHT											Approx 13 kg (4.4 lb)																																
PUSHING FORCE												Up to 200 N (Up to 45 lbf)											BATTERY											18 V, 5Ah Milwaukee																																		
JETTING V2	CABLE DIAMETER IN MM	0.8	1	2,4	3	4	5	6	7	8	9																																																									